



UFO-STRONG Series

VIGOROUSLY IMPROVING WORK ENVIRONMENT EFFICIENCY.

Powered by

tuya[®]

Intelligence
Inside

UFO STRONG



Parameters

Model	Power	LED Qty	Luminous Flux	Efficacy	Size
UFOB-100W	100W	3030SMD140LEDS	11000LM	110Lm/W	Ø290*H160mm
UFOB-150W	150W	3030SMD210LEDS	16000LM	106Lm/W	Ø340*H170mm
UFOB-200W	200W	3030SMD280LEDS	20000LM	100Lm/W	Ø390*H180mm

Input Voltage: AC85-265V
 Frequency: 50/60Hz
 Power Factors: ≥ 0.5
 CCT: 3000 ~ 6500K
 CRI: Ra ≥ 80
 Beam Angle: 60°
 Main Material: Aluminum+PS
 Body Color: Sand Black
 Input Cable: 0.5mm²
 Installation: Suspended
 Protection: IP65
 Environment: -20°C ~ 50°C
 Longevity: 20000h
 Driver: Simeng Constant Current

Packing

Model	Weight/PC	Qty/CTN	Inner Box Size	Master CTN
UFOB-100W	2.88kgs	1	-	32*32*17cm
UFOB-150W	3.8kgs	1	-	36*36*17cm
UFOB-200W	4.88kgs	1	-	42*42*22.5cm

DETAILS

